

# Appliance Comparison Chart

## 2012 Appliances

	2200	4200	4600	4800	12200	12400	12600	21400	61000
	Small-Office	Enterprise Grade			Data Center Grade			Ultra-High End	
<b>Performance</b>									
SecurityPower	114	114	374	623	738	1046	1861	2003/2900 <sup>1</sup>	3000 to 14600
Firewall Throughput (Gbps)	3	3	9	11	15	25	30	50/100 <sup>1</sup>	Up to 200
IPS Default Profile (Gbps)	2	2	4	6	8	12	17	21	Up to 85
Connections Per Second (K)	25	25	50	70	90	110	130	120/300 <sup>2</sup>	Up to 600
Concurrent Sessions (M)	1.2	1.2	1.2	3.5 <sup>2</sup>	3.5 <sup>2</sup>	3.5 <sup>2</sup>	3.5 <sup>2</sup>	10 <sup>2</sup>	Up to 70
<b>Network</b>									
10/100/1000Base-T/Max Ports	6/6	4/8	8/12	8/16	8/16	10/26	14/26	13/37	NA
1000Base-F SFP (MAX Ports)	NA	4	4	4	4	12	12	36	NA <sup>3</sup>
10GBase-F SFP+ (MAX Ports)	NA	NA	NA	2	4	12	12	12	16/32 <sup>3</sup>
40GBase-F MAX Ports	NA	NA	NA	NA	NA	NA	NA	NA	4 <sup>3</sup>
Expansion Slot	0	1	1	1	1	3	3	3	14
<b>Additional Features</b>									
Software Edition	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R75.x 64 bit
Storage	250 GB	250 GB	250 GB	250 GB	1+1 500 GB	1+1 500 GB	2x500 GB RAID 1	2x500 GB RAID 1	-
Memory / Max	2/2 GB	4/4 GB	4/4 GB	4/8 GB	4/12 GB	4/12 GB	6/12 GB	12/24 GB	12/24 GB <sup>5</sup>
LOM Card (Optional)	NA	NA	NA	Yes	Yes	Yes	Yes	Yes	Included
<b>Physical</b>									
Enclosure	Desktop	1U	1U	1U	1U	2U	2U	2U	15U
Dimensions WxDxH (Standard)	8.27 x 8.25 x 1.65 in.	17.25 x 12.56 x 1.73 in.	17.25 x 12.56 x 1.73 in.	17.25 x 16.14 x 1.73 in.	17.25 x 16.14 x 1.73 in.	17.24 x 22.13 x 3.46 in.	17.24 x 22.13 x 3.46 in.	17 x 28 x 3.5 in.	17.5 x 15.16 x 26.25 in.
Dimensions WxDxH (Metric)	210 x 209.5 x 42 mm	439 x 319 x 44 mm	439 x 320 x 44 mm	438 x 410 x 44 mm	438 x 410 x 44 mm	438 x 562 x 88 mm	438 x 562 x 88 mm	431 x 710 x 88 mm	445 x 385 x 660 mm
Weight	2kg (4.4 lbs)	4kg (8.82 lbs)	7.5kg (16.53 lbs)	7.6kg (16.76 lbs)	7.6kg (16.76 lbs)	23.4kg (51.6 lbs)	23.4kg (51.6 lbs)	26kg (57.4 lbs)	Max: 90kg (198.4 lbs)
<b>Power</b>									
Dual, Hot-Swappable Power Supplies	No	No	No	Optional	Optional	Yes	Yes	Yes	Yes <sup>6</sup>
Power Input	100-240VAC, 47-63Hz								
Single Power Supply Rating	100W	100W	250W	275W	275W	300W	400W	910W	1200W @ 110V, 1600W @ 220V
Power Consumption (Max)	35W	57W	90W	140W	121W	132W	220W	449W	-
DC Option	No	No	No	No	No	No	No	No	Yes

<sup>1</sup> With acceleration card in 2012

<sup>2</sup> With software upgrade in 2012

<sup>3</sup> Not including Security Switch Module Management Ports

<sup>4</sup> Maximum of 256 VLANs per Interface

<sup>5</sup> Per Security Gateway Module

<sup>6</sup> Includes 5 AC PSUs or 2 DC PSUs



# Appliance Comparison Chart

## UTM-1 Appliances

	UTM-1 Edge X ADSL / W ADSL	UTM-1 Edge N UTM-1 Edge NW	Series 80	130	270	570	1070	2070	3070
<b>Performance</b>									
SecurityPower	-	-	-	50	50	101	101	101	298
Firewall Throughput	190 Mbps	1.0 Gbps	1.5 Gbps	1.5 Gbps	1.5 Gbps	2.5 Gbps	3 Gbps	3.5 Gbps	4.5 Gbps
VPN Throughput	35 Mbps	200 Mbps	220 Mbps	120 Mbps	120 Mbps	300 Mbps	350 Mbps	450 Mbps	1100 Mbps
IPS Default Profile	35 Mbps	180 Mbps	720 Mbps	1 Gbps	1 Gbps	1.7 Gbps	2.2 Gbps	2.7 Gbps	4 Gbps
Connections Per Second (K)	-	-	-	10	10	19	25	31	54
Concurrent Sessions	8,000	60,000	150,000	600,000	600,000	650,000	650,000	1,100,000	1,100,000
<b>Network</b>									
10/100Base-T/Max Ports	6	-	-	1	-	-	-	-	-
10/100/1000Base-T/Max Ports	-	6	10	4	4	6	6	8	10
VLANs	32	64	1024	1024 <sup>1</sup>	1024 <sup>1</sup>	1024 <sup>1</sup>	1024 <sup>1</sup>	1024 <sup>1</sup>	1024 <sup>1</sup>
<b>Additional Features</b>									
Software Edition	Embedded NGX	Embedded NGX	R71	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75
Storage	-	-	-	80 GB	160 GB	160 GB	160 GB	160 GB	160 GB
Licensed Users	8/16	32/U	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Multisite Management	No	No	No	Standalone	Yes	Yes	Yes	Yes	Yes
<b>Physical</b>									
Enclosure	Desktop	Desktop	Desktop	Desktop	1U	1U	1U	1U	1U
Dimensions (Standard)	1.2 x 8 x 4.8 in.	1.2 x 8 x 4.8 in.	8.75 x 1.75 x 6 in.	10.6 x 5.7 x 1.6 in.	16.8 x 10 x 1.73 in.	16.8 x 10 x 1.73 in.	16.8 x 10 x 1.73 in.	17.4 x 15 x 1.73 in.	17.4 x 15 x 1.73 in.
Dimensions (Metric)	30 x 203 x 122mm	30 x 203 x 122mm	22 x 4.4 x 15.24 cm	270 x 145 x 40mm	429 x 255 x 44mm	429 x 255 x 44mm	429 x 255 x 44mm	443 x 381 x 44mm	443 x 381 x 44mm
Weight	0.7kg (1.6lbs)	0.7kg (1.6lbs)	8 lbs (3.6 kg)	1.6kg (3.52lbs)	3.7kg (8.1lbs)	3.7kg (8.1lbs)	3.7kg (8.1lbs)	6.5kg (14.3lbs)	6.5kg (14.3lbs)
<b>Power</b>									
Power Input	100/240V, 50/60Hz								
Single Power Supply Rating	18W	18W	12V/2A DC 24W	60W	65W	65W	65W	250W	250W
Power Consumption (Max)	-	-	16.68W	46.9W	26.2W	41.1W	40.1W	63.1W	77.5W

<sup>1</sup> Maximum of 256 VLANs per interface



## Power-1 Appliances

	Power-1 5077	Power-1 9077	11067	Power-1 11000 Series 11077	11087
<b>Performance</b>					
SecurityPower	596	1006	up to 1222	up to 1222	1222
Firewall Throughput <sup>1</sup> (Gbps)	9	16	15	20	30
VPN Throughput (Gbps)	2.4	3.7	3.7	4	4.5
IPS Default Profile <sup>2</sup> (Gbps)	7.5	10	10	12	15
Connections Per Second (K)	77	77	77	95	105
Concurrent Sessions (M)	1.2	1.2	1.2	1.2	1.2
<b>Network</b>					
10/100/1000Base-T/Max Ports	10/14	14/18	14/18	14/18	14/18
1000Base-F SFP Max Ports	4	8	8	8	14/18
10GBase-F SFP Max Ports	2	4	4	4	4
Expansion Slots	1	2	2	2	2
VLANs	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>
<b>Additional Features</b>					
Software Edition	R65, R70, R71, R75	R65, R70, R71, R75	R70, R71, R75	R70, R71, R75	R70, R71, R75
Storage	160 GB	2 x 160 GB	2 x 250 GB	2 x 250 GB	2 x 250 GB
LOM Card Option	Yes	Yes	Yes	Yes	Yes
<b>Physical</b>					
Enclosure	2U	2U	2U	2U	2U
Dimensions WxDxH (Standard)	17 x 20 x 3.46 in.	17 x 20 x 3.46 in.	17 x 22.8 x 3.46 in.	17 x 22.8 x 3.46 in.	17 x 22.8 x 3.46 in.
Dimensions WxDxH (Metric)	431 x 509.5 x 88mm	431 x 509.5 x 88mm	431 x 580 x 88mm	431 x 580 x 88mm	431 x 580 x 88mm
Weight	14.5kg (31.9 lbs)	16.5kg (36.3 lbs)	23.4kg (51.6 lbs)	23.4kg (51.6 lbs)	23.4kg (51.6 lbs)
<b>Power</b>					
Dual, Hot-Swappable Power Supplies	Included	Included	Included	Included	Included
Power Input	100~240V, 50~60Hz				
Single Power Supply Rating	250W	400W	500W	500W	500W
Power Consumption (Max)	164.1W	200.7W	253.2W	253.2W	253.2W

<sup>1</sup> Performance data represents the maximum capabilities of the systems as measured under optimal testing conditions. Deployment and policy considerations may impact performance results.

<sup>2</sup> Test based on real-world traffic blend using the default profile

<sup>3</sup> Maximum of 256 VLANs per interface



# Appliance Comparison Chart

## IP Appliances

	IP282	IP297	IP397	IP567	IP697	IP1287	IP2457
<b>Performance</b>							
SecurityPower	113	113	116	116	268	670	1112
Firewall Throughput (Gbps)	1.5	1.5	3.0	7	7.2/11.7 <sup>2</sup>	10.3/17.5 <sup>2</sup>	11/30 <sup>2</sup>
VPN Throughput (Gbps)	1.0	1.0	677 Mbps	1.7	1.9/ 3.3 <sup>2</sup>	1.9/8.3 <sup>2</sup>	1.9/8.3 <sup>2</sup>
IPS Default Profile (Gbps)	1.4	1.4	2.9	2.9	4	7	9
Connections Per Second (K)	-	30	35	35	55	73	81
Concurrent Sessions	900,000	900,000	1 million	1 million	1 million	1 million	1 million
<b>Network</b>							
10/100/1000Base-T/Max Ports	6	6/8	4/8	4/12	4/16	4/28	4/32
1000Base-F SFP Max Ports	NA	2	4	4	8	12	12
10GBase-F SFP+ Max Ports	NA	NA	NA	NA	6 <sup>1</sup>	10 <sup>1</sup>	10 <sup>1</sup>
Expansion Slots	NA	1	2	2	3	5	5
VLANs	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>	1024 <sup>3</sup>
<b>Additional Features</b>							
Software Edition	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75
Storage	40 GB	40 GB	80 GB	80 GB	80 GB	80 GB	80 GB
Disk-Based or Flash	Disk	Disk or Flash	Disk or Flash	Disk or Flash	Disk or Flash	Disk or Flash	Disk or Flash
Memory / Max	1/2	1/2	1/2	1/2	2/4	4/8	4/8
ADP Module	NA	NA	NA	NA	Optional	Optional	Optional
VPN Acceleration	Optional	Optional	Included	Included	Included	Included	Included
<b>Physical</b>							
Enclosure	1U/Half rack	1U/half rack	1U	1U	1U	2U	2U
Dimensions WxDxH (Standard)	8.52 x 18 x 1.71 in.	8.52 x 18 x 1.71 in.	17 x 16 x 1.71 in.	17.23 x 22 x 1.71 in.	17.23 x 24 x 1.71 in.	17.23 x 24.11 x 3.46 in.	17.23 x 24.11 x 3.46 in.
Dimensions WxDxH (Metric)	216 x 457 x 44 mm	216 x 457 x 44mm	432 x 406 x 44mm	438 x 559x 44mm	438 x 610x 44mm	438 x 613 x 88mm	438 x 613 x 88mm
Weight	5.1kg (11.25 lbs)	5.1kg (11.25 lbs)	7.71kg (17.0 lbs)	11.84kg (26.1 lbs)	12.38kg (27.3 lbs)	19.6kg (43.2 lbs)	20.57kg (45.35 lbs)
<b>Power</b>							
Dual, Hot-Swappable Power Supplies	No	No	No	No	Included	Included	Included
Power Input	100/240V 50/60Hz	100/240V, 50/60Hz					
Single Power Supply Rating	133W	133W	150W	225W	250W	700W	700W
Power Consumption (Max)	-	-	100W	165W	-	-	-
DC Option	NA	NA	NA	NA	NA	Optional	Optional

<sup>1</sup> Optional

<sup>2</sup> Performance without ADP/with ADP

<sup>3</sup> Maximum of 256 VLANs per interface



# Appliance Comparison Chart

## IAS Series Appliances

	IAS <sup>1</sup> D1	IAS <sup>1</sup> D2	IAS <sup>1</sup> D6	IAS <sup>1</sup> D8	IAS <sup>1</sup> M2	IAS <sup>1</sup> M6	IAS <sup>1</sup> M8	IAS <sup>1</sup> R2	IAS <sup>1</sup> R6	IAS <sup>1</sup> R8
<b>Performance</b>										
Firewall Throughput <sup>2</sup> (Gbps)	2	7	16	20	7	16	20	7	16	20
VPN Throughput <sup>2</sup> (Gbps)	1.2	2.4	3	4	2.4	3	4	2.4	3	4
IPS Default Profile <sup>3</sup> (Gbps)	-	4	7.1	8.6	4	7.1	8.6	4	7.1	8.6
Concurrent Sessions (M)	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
<b>Network</b>										
10/100/1000Base-T/Max Ports	6/6	6/10	6/10	8/18	4/10	10/10	14/18	4/10	10/10	14/24
VLANs	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>	1024 <sup>4</sup>
<b>Additional Features</b>										
Software Edition	R65, R70, R75	R65, R70, R75	R65, R70, R75	R65, R70, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R75	R65, R70, R75	R65, R70, R75
Storage	2 x 160 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB	2 x 73 GB	2 x 73 GB	2 x 73 GB	2 x 146 GB (8 max)	2 x 146 GB (8 max)	2 x 146 GB (12 max)
UTM Out of the Box	Optional	Optional	Optional	Optional	Yes	Optional	Optional	Optional	Optional	Optional
Multisite Management	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
<b>Physical</b>										
Enclosure	1U	1U	1U	2U	1U	1U	2U	1U	1U	2U
Dimensions WxDxH (Standard)	17.6 x 27.5 x 1.69 in.	16.78 x 27.5 x 1.70 in.	16.78 x 27.5 x 1.70 in.	17.5 x 27.5 x 3.38 in.	17.3 x 27.5 x 1.75 in.	17.3 x 27.5 x 1.75 in.	17.5 x 27.5 x 3.36 in.	17 x 30 x 1.70 in.	17 x 30 x 1.70 in.	17.5 x 30.3 x 3.38 in.
Dimensions WxDxH (Metric)	439 x 698 x 43 mm	426 x 692 x 43 mm	426 x 692 x 43 mm	426 x 743 x 86 mm	440 x 698 x 44 mm	443 x 698 x 44 mm	444 x 698 x 84.8 mm	431 x 762 x 43 mm	431 x 762 x 43 mm	445 x 770 x 86 mm
Weight	14.3kg (35.5 lbs)	17.92kg (39.5 lbs)	17.92kg (39.5 lbs)	20.3kg (60 lbs)	16.1kg (35.5 lbs)	16.1kg (35.5 lbs)	26.1kg (57.5 lbs)	17kg (37.5 lbs)	17.92kg (39.5 lbs)	25kg (55 lbs)
<b>Power</b>										
Dual, Hot-Swappable Power Supplies	Optional	Optional	Optional	Included	Optional	Optional	Included	Optional	Optional	Included
Power Input	100~240V, 47~63Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 47~63Hz	100~240V, 47~63Hz	100~240V, 47~63Hz
Single Power Supply Rating	400W	750W	750W	1200W	650W	650W	1300W	450W	450W	800W
Power Consumption (Max)	180W	212W	212W	342W	180W	212W	342W	178W (min)	178W (min)	504W

<sup>1</sup> IAS = Integrated Appliance Solutions

<sup>2</sup> Performance data represents the maximum capabilities of the systems as measured under optimal testing conditions. Deployment and policy considerations may impact performance results.

<sup>3</sup> Test based on real-world traffic blend using the default profile

<sup>4</sup> Maximum of 256 VLANs per interface



# Appliance Comparison Chart

## VSX Appliances

	VSX 12200 Single Unit	VSX 12200 VSLs	VSX 12400 Single Unit	VSX 12400 VSLs	VSX 12600 Single Unit	VSX 12600 VSLs	VSX 21400 Single Unit	VSX 21400 VSLs
<b>Network</b>								
10/100/1000Base-T Port / (max)	8/16	16/32	10/26	20/52	14/26	28/52	13/37	26/74
1000Base-F SFP (Max Ports)	4	8	12	24	12	24	12	24
10GBase-F SFP+ (Max Ports)	4	8	12	24	12	24	12	24
Expansion Slot	1	2	3	6	3	6	3	6
VLANs	4096	4096	4096	4096	4096	4096	4096	4096
<b>Additional Features</b>								
Software Edition	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67
Storage	1 + 1 500 GB	2 x 1 + 1 500 GB	1 + 1 500 GB	2 x 1 + 1 500 GB	2 x 500 GB RAID 1	2 x 2 x 500 GB RAID 1	2 x 500 GB RAID 1	2 x 2 x 500 GB RAID 1
Memory Max	4/12 GB	2 x 4/12 GB	4/12 GB	2 x 4/12 GB	6/12 GB	2 x 6/12 GB	12/24 GB	2 x 12/24 GB
LOM Card Option	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Virtual Systems (Included/Capacity)	5/10	5/10	10/50	10/50	10/150	10/150	10/250	10/250
<b>Physical</b>								
Enclosure	1U	2U	2U	4U	2U	4U	2U	4U
Dimensions WxDxH (Standard)	17.25 x 16.14 x 1.73 in.	17.25 x 16.14 x 3.46 in.	17.25 x 22.13 x 3.46 in.	17.25 x 22.13 x 6.92 in.	17.24 x 22.13 x 3.46 in.	17.25 x 22.13 x 6.92 in.	17 x 28 x 3.5 in.	17 x 28 x 7 in.
Dimensions WxDxH (Metric)	438 x 410 x 44mm	438 x 410 x 88mm	438 x 562 x 88mm	438 x 562 x 176mm	438 x 562 x 88mm	438 x 562 x 176mm	431 x 710 x 88mm	431 x 710 x 176mm
Weight	7.6kg (16.76 lbs)	15.2kg (33.52 lbs)	23.4kg (51.6 lbs)	46.8kg (103.2 lbs)	23.4kg (51.6 lbs)	46.8kg (103.2 lbs)	26kg (57.4 lbs)	52kg (114.8 lbs)
<b>Power</b>								
Dual, Hot-Swappable Power Supplies	Optional	Optional	Yes	Yes	Yes	Yes	Yes	Yes
Power Input	100~240V, 47~63Hz							
Single Power Supply Rating	275W	275W	300W	300W	400W	400W	910W	910W
Power Consumption (Max)	121W	2 x 121W	132W	2 x 132W	220W	2 x 220W	449W	2 x 449W



# Appliance Comparison Chart

## VSX Appliances continued

	VSX-1 3070 Single Unit	VSX-1 9070 Single Unit	VSX-1 9090 VSLs	VSX-1 11000 Single Unit	VSX-1 11000 VSLs
<b>Performance</b>					
Firewall Throughput (Gbps)	4.5	13.5	27	15/20/25	30/40/50
VPN Throughput (Gbps)	1.0	3.6	7.2	3.7/4.0/4.5	7.4/8.0/9.0
Concurrent Sessions (M)	1	1.1	1.6	1.2	1.6
<b>Network</b>					
10/100/1000Base-T/Max Ports	10	14	28	14	28
1000Base-F SFP Max Ports	NA	8	16	8	16
10GBase-F SFP+ Max Ports	NA	4	8	4	8
Expansion Slots	NA	2	4	2	4
VLANs	4096	4096	4096	4096	4096
<b>Additional Features</b>					
Software Edition	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67
Storage	160 GB	2 x 160 GB	4 x 160 GB	2 x 250 GB	4 x 250 GB
LOM Card Option	Yes	Yes	Yes	Yes	Yes
Virtual Systems (Included/Capacity)	5/10	10/150	10/150	10/250	10/250
<b>Physical</b>					
Enclosure	1U	2U	4U	2U	4U
Dimensions (Standard)	17.4 x 15 x 1.73 in.	17 x 20 x 3.46 in.	17 x 20 x 7 in.	17 x 20 x 3.46 in.	17 x 20 x 7 in.
Dimensions (Metric)	443 x 381 x 44mm	431 x 509.5 x 88mm	431 x 509.5 x 176mm	431 x 509.5 x 88mm	431 x 509.5 x 176mm
Weight	6.5kg (14.3 lbs)	16.5kg (36.3 lbs)	33kg (72.6 lbs)	23.4kg (51.6 lbs)	46.8kg (103.2 lbs)
<b>Power</b>					
Dual, Hot-Swappable Power Supplies	No	Yes	Yes	Yes	Yes
Power Input	100/240V, 50/60Hz				
Single Power Supply Rating	250W	400W	400W	500W	500W
Power Consumption (Max)	78W	201W	2 x 201W	253W	2 x 253W



## DLP-1 Appliances

	DLP-1 2571	DLP-1 9571
<b>Performance</b>		
Number of Users	1000	5000
Messages / Hour	70,000	350,000
Throughput	700 Mbps	2.5 Gbps
<b>Network</b>		
10/100/1000Base-T/Max ports	6/6	10/14
10/100/1000Base-T/Max ports	NA	8
10GBase-F SFP+ Max Ports	NA	4
Expansion Slots	NA	2
VLANs	1024	1024
<b>Additional Features</b>		
Software Edition	R75	R75
Storage	500GB	2 x 2TB (Mirrored – RAID 1)
LOM Card Option	No	Yes
Bypass Card	Optional	Included
<b>Physical</b>		
Enclosure	1U	2U
Dimensions WxDxH (Standard)	17.4 x 15 x 1.73 in.	17 x 20 x 3.46 in.
Dimensions WxDxH (Metric)	443 x 381 x 44mm	431 x 509.5 x 88mm
Weight	6.5kg (14.3 lbs)	16.5kg (36.3 lbs)
<b>Power</b>		
Dual, Hot-Swappable Power Supplies	No	Yes
Power Input	100 ~ 240V; 50 ~ 60Hz	
Single Power Supply Rating	250W	400W
Power Consumption (Max)	77.5W	200.7W



## Software Blades Appliance Comparison Chart

	2205	2207	2208	2210	4205	4207	4208	4210	4607	4608	4610	4807	4808	4810
<b>Security Gateway Software Blades</b>														
Firewall	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Identity Awareness	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Advanced Networking & Clustering	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mobile Access <sup>1</sup>	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPS	*	✓	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓
Application Control	*	✓	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓
DLP	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓	*
URL Filtering	*	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓
Antivirus & Anti-Malware	*	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓
Anti-Spam & Email Security	*	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓
Web Security	*	*	*	*	*	*	*	*	*	*	*	*	*	*
<b>Security Management Software Blades</b>														
Network Policy Management	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Logging & Status	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

<sup>1</sup> Mobile Access for 5 users is included in default package – to extend the package use the Mobile Access packages

**Optional Security Management Software Blades available:**

SmartWorkflow, Monitoring, Management Portal, User Directory, SmartProvisioning, SmartReporter, SmartEvent, Endpoint Policy Management

✓ = Included      \* = Optional      NA = Not Available



## Software Blades Appliance Comparison Chart continued

	12207	12208	12210	12407	12408	12410	12607	12608	12610	21412	61005
<b>Security Gateway Software Blades</b>											
Firewall	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Identity Awareness	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Advanced Networking & Clustering	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mobile Access <sup>1</sup>	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	NA
IPS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	*
Application Control	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	*
DLP	*	✓	*	*	✓	*	*	✓	*	✓	NA
URL Filtering	*	*	✓	*	*	✓	*	*	✓	✓	*
Antivirus & Anti-Malware	*	*	✓	*	*	✓	*	*	✓	✓	*
Anti-Spam & Email Security	*	*	✓	*	*	✓	*	*	✓	✓	NA
Web Security	*	*	*	*	*	*	*	*	*	*	NA
<b>Security Management Software Blades</b>											
Network Policy Management	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	NA
Logging & Status	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	NA

<sup>1</sup> Mobile Access for 5 users is included in default package – to extend the package use the Mobile Access packages

### Optional Security Management Software Blades available:

SmartWorkflow, Monitoring, Management Portal, User Directory, SmartProvisioning, SmartReporter, SmartEvent, Endpoint Policy Management

✓ = Included      \* = Optional      NA = Not Available



## Software Blades Appliance Comparison Chart continued

	Series 80	UTM-1 132	UTM-1 134	UTM-1 138	UTM-1 272	UTM-1 274	UTM-1 278	UTM-1 574	UTM-1 578	UTM-1 1075	UTM-1 1078	UTM-1 2075	UTM-1 2078	UTM-1 3075	UTM-1 3078
<b>Security Gateway Software Blades</b>															
Firewall	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Application Control	NA	*	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Identity Awareness	NA	*	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPS	*	*	*	✓	*	*	✓	*	✓	✓	✓	✓	✓	✓	✓
DLP	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
URL Filtering	*	*	*	✓	*	*	✓	*	✓	*	✓	*	✓	*	✓
Antivirus & Anti-Malware	*	*	*	✓	*	*	✓	*	✓	*	✓	*	✓	*	✓
Anti-Spam & Email Security	*	*	*	✓	*	*	✓	*	✓	*	✓	*	✓	*	✓
Advanced Networking	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Mobile Access	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Acceleration & Clustering	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
<b>Security Management Software Blades</b>															
Network Policy Management	NA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Endpoint Policy Management	NA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Logging & Status	NA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

**Optional Security Gateway Software Blades available:**

Voice over IP (VoIP), Web Security

**Optional Security Management Software Blades available:**

SmartWorkflow, Monitoring, Management Portal, User Directory, SmartProvisioning, SmartReporter, SmartEvent, Endpoint Policy Management

✓ = Included      \* = Optional      NA = Not Available



## Software Blades Appliance Comparison Chart continued

	Power-1 5077	Power-1 9077	Power-11067	Power-11077	Power-11087
<b>Security Gateway Software Blades</b>					
Firewall	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓
Advanced Networking	✓	✓	✓	✓	✓
Acceleration & Clustering	✓	✓	✓	✓	✓
Identity Awareness	✓	✓	✓	✓	✓
IPS	✓	✓	✓	✓	✓
Application Control	✓	✓	✓	✓	✓
URL Filtering	*	*	*	*	*
Antivirus & Anti-Malware	*	*	*	*	*
Anti-Spam & Email Security	*	*	*	*	*
DLP	*	*	*	*	*
Mobile Access	*	*	*	*	*

	IP282	IP297	IP397	IP567	IP697	IP1287	IP2457
<b>Security Gateway Software Blades</b>							
Firewall	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓
Application Control	*	✓	✓	✓	✓	✓	✓
Identity Awareness	*	✓	✓	✓	✓	✓	✓
IPS	*	✓	✓	✓	✓	✓	✓
Advanced Networking	*	✓	✓	✓	✓	✓	✓
Acceleration & Clustering	*	✓	✓	✓	✓	✓	✓
URL Filtering	*	*	*	*	*	*	*

**Optional Security Gateway Software Blades available:** Voice over IP (VoIP), Web Security

✓ = Included    \* = Optional    NA = Not Available

